



SOCB25082A

Serve Over Counter

Product Features

- Excellent product visibility
- 825 mm deep stainless steel deck
- Anti mist front glass
- Glass front opens forward for easy cleaning
- Stainless steel rear shelf
- Ventilated cooling
- Temperature Class 3M1
- LED top light
- 2 x 220V sockets to rear
- Multiplexing kit as accessory
- Bumper bars

Ventilated serve over deli counter

The SOCB range of serve over counters is the perfect choice for delis wanting a nice display for their prepared meals, meats, and cheeses. The 825 mm deep deck is made from stainless steel and is illuminated by LED lights in the top of the unit. The counter is open to the back and easily accessible for the staff. The glass front conveniently opens forward for easy cleaning. The display deli counter comes with a storage compartment with wide doors that accommodate standard E2 vegetable boxes. The SOC range can be multiplexed to create a complete counter solution. Each unit has two 220V sockets so you can connect e.g. a cash register. To customize the serve over counter for your needs, it is possible to choose from a wide range of accessories such as: an extra shelf (for e.g. a cash register), a knife block, mobile plexi glass dividers, shelves for creating different levels, red lights for butchers, and a two level holder for GN-pans. It is also possible to make factory orders for SOC serve over counters for different purposes and temperature ranges. Please contact our sales team for more information.

Measures and Content

Total Display Area	m ²	2.29
Temperature Range	°C	0 to +4
Climate Class		3
Gross / Net Weight	kg	410 / 325
Gross / Net Volume	l	627

Design and Material

Door No & Type	
Tempered glass	Yes
Shelves No & Type	
Feet / Legs	Adjustable feet
Exterior Finish	Grey RAL7015
Interior Finish	Stainless Steel
Interior Light	LED
Lock	No

Cooling and Functions

Type of Controller	Electronic
Type of Cooling	Ventilated
Type of Defrost	Automatic-Electric
Refrigerant	R290
Refrigerant Charge	g2 x 150
Thermometer	Yes

Power and Consumption

Energy Class		F
Energy Consumption	kWh/24h	10.2
Annual Energy Cons.	kWh/year	3723
Power		1
Input Power	W	860
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	59

Dimensions

Internal Dimension (WxDxH)	mm	2500 x 825 x
External Dimension (WxDxH)	mm	2548 x 1120 x 1190
Packed Dimension (WxDxH)	mm	2750 x 1250 x 1400
40ft Container Load	pcs	4

