

## BA26SS

### Backbar Cooler

#### Product Features

- EU Energy Class A
- Approx. 59% more energy efficient than previous BA-range
- Stainless steel exterior
- Double glazed tempered glass
- Energy saving variable speed compressor
- Self-closing sliding glass doors
- Ventilated cooling for fast pull-down and even temperature
- Easy access electronic thermostat
- Adjustable shelves behind each door
- LED interior light

#### High-quality backbar with low energy consumption

The BA is our range of high-quality backbars. It has been updated and now uses in average 59% less energy compared to the previous models from the same range. This backbar has ventilated cooling for a short pull-down time to ensure that you can keep up with customer demand for cold beverages. If you need to adjust the temperature this is easily done on the electronic thermostat. The backbar cooler is made of solid materials and has adjustable chrome shelves with closely-spaced wires, which gives you a high capacity and stability. Furthermore, it has self-closing aluminium sliding doors with double glazed tempered glass. This helps save energy, but it also means a great product visibility.

#### Measures and Content

Total Display Area	m <sup>2</sup>	0.52
Temperature Range	°C	+2 to +10
Climate Class		4
Gross / Net Weight	kg	77 / 72
Gross / Net Volume	l	191 / 183

#### Design and Material

Door No & Type	2 sliding glass doors	
Door Reversible	No	
Tempered glass	Yes	
Shelves No & Type	4 wire shelves chrome	
Shelf Color	Chrome	
Shelf Dimensions	395x330 mm	
Feet / Legs	4 adjustable feet	
Exterior Finish	Stainless steel	
Interior Finish	Stucco aluminium	
Interior Light	LED	
Lock	Yes	

#### Cooling and Functions

Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic	
Refrigerant	R600a	
Refrigerant Charge	g	70
Thermometer	Yes	

#### Power and Consumption


Energy Class	A	
Energy Consumption	kWh/24h	1.14
Annual Energy Cons.	kWh/year	416
Max Ambient	30°C at 55% RH	
Input Power	W	115
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	45

#### Dimensions

Internal Dimension (WxDxH)	mm	810 x 345 x 720
External Dimension (WxDxH)	mm	900 x 515 x 870
Packed Dimension (WxDxH)	mm	1000 x 600 x 950
40ft Container Load	pcs	96



Protective thermostat cover



Adjustable shelves