

STB MODULE

Bakery oven / pizza



Ref. 710580



TECHNICAL CHARACTERISTICS	FEATURES
<p>Electric power 5400 W</p> <p>Maximum temperature 350 °C</p> <p>Weight 100 kg</p> <p>Voltage 400 V-50/60 Hz</p> <p>Connection Three phase 3F+N+T</p> <p>Internal dimensions (W)670x(D)525x(H)180 mm</p> <p>External dimensions (W)800x(D)905x(H)385 mm</p> <p>Humidity sistem optional</p>	<ul style="list-style-type: none">• 5" touch screen• Independent up and floor temperature regulation• Maximum temperature 350 °C• Energy saving mode• Up to 6 cooking stages• Recipe book• Steam-control / programmable chimney• Programmable automatic turn on• Humidity system

DECLARACIÓN UE DE CONFORMIDAD EU DECLARATION OF CONFORMITY

Directiva(s) del Consejo con la(s) que se declara conformidad:

Council Directive(s) to which conformity is declared:

DC 2014/35/EU + DC 2014/30/EU + DC 2011/65/EU

Aplicación de las Normas:

Application of the Standards:

UNE-EN 60335-1:2012 + AC:2014 + A11:2014 + A13:2017 + A14:2014 + A2:2020 + A1:2020; UNE-EN 60335-2-42:2004 + Corr:2007 + A1:2008 + A11:2012; UNE-EN 55014-1:2017 + A11:2021; UNE-EN 55014-2:2015; UNE-EN 61000-3-2:2014; UNE-EN 61000-3-3:2013 + A1:2020

Fabricante / *Manufacturer's name:*

**FM CALEFACCIÓN S.L.
CIF: B-14343594**

Dirección / *Manufacturer's address:*

**CTRA. de Rute km.2.700, C.P.:14900, Lucena
Cordoba, Spain**

Tipo de aparato / *Type of device:*

HORNO

Marca / *Trade.:*

FM CALEFACCIÓN

Modelo / *Model no.:*

STB Module N/S: 21XXXXXXXXXX

Nosotros, los abajo firmantes, declaramos bajo nuestra exclusiva responsabilidad que el equipo especificado cumple con la(s) Directiva(s) y Norma(s) mencionadas

We, the undersigned, hereby declare under our sole responsibility that the specified equipment is in conformity with the above Directive(s) and Standard(s)

Lugar / *Place:* **Lucena**

Firma / *Signature:* **B-14343594**

Fecha / *Date:* **01/01/2021**



STB Module



TECHNICAL CHARACTERISTICS		CONEXIONADO	
Empty unit weight		1	On/Off button
Unit+packaging weight		2	Manguera alimentación
Supply voltage	400 Vac - three phase	3	Safety gap $\geq 120\text{mm}$
Frequency	50/60 Hz	4	Fumes exit $\varnothing 50\text{ mm}$
Power cable	Hose 3F+N+T 4 mm ²	5	USB Connection
Sound pressure level	Below 70 dB	6	Water connection 3/4"
Total power	5400 W	7	Nameplate
Thermal power	5400 W		

*Dimensions in mm

